

Medidas de tuercas Rosca Milimétrica

Diámetro	Hexágono	Altura	Entre aristas
0/7	0.500	12,700	-
0/6	0.464	11,785	-
0/5	0.432	10,973	-
0/4	0.400	10,160	-
0/3	0.372	9,449	0.500
0/2	0.348	8,839	0.445
0	0.324	8,230	0.396
1	0.300	7,620	0.353
2	0.276	7,010	0.315
3	0.252	6,401	0.280
4	0.232	5,893	0.250
5	0.212	5,385	0.223
6	0.192	4,877	0.198
7	0.176	4,470	0.178
8	0.160	4,064	0.157
9	0.144	3,658	0.140
10	0.128	3,251	0.125
11	0.116	2,946	0.111
12	0.104	2,642	0.099
13	0.092	2,337	0.083
14	0.080	2,032	0.079
15	0.072	1,829	0.070
16	0.064	1,626	0.063
17	0.056	1,422	0.056
18	0.048	1,219	0.050
19	0.040	1,016	0.0440

Rosca en pulgadas

Diámetro	Hexágono	Altura	Entre aristas
3/8	17.4	9.5	19.7
7/16	19	11	22
1/2	22.2	12.7	25.4
9/16	23.8	14	27
5/8	27	15.5	31.2
3/4	31.7	19	35.7
7/8	36	22	41.6
1	41.2	25	47.2

1 1/8	46	28	52
1 1/4	50	31	57.8
1 3/8	55	34	63.5
1 1/2	60	38	69.3
1 5/8	65	41	75
1 3/4	69.8	44	78.6
1 7/8	74.6	47	85.5
2	79.3	50	90
2 1/4	88.9	56	100
2 1/2	98.4	62	111.6
2 3/4	108	70	124
3	118	76	135.3
3 1/4	127	80	147
3 1/2	137	87	157
3 3/4	146	93	169
4	156	100	179.5